



### Cable ties with integrated RFID transponder

#### T50RFID – Low Frequency (LF) and High Frequency (HF)

RFID cable ties provide an innovative solution for clear and rapid product identification. The nylon cable ties are equipped with an RFID transponder and therefore combine the numerous advantages of a regular cable tie with RFID technology. The ties are especially suited for securing, serialisation, tracking and identification of products in the areas of resource management, electrical inspection, inventory, distribution and rental services as well as for easy management of maintenance and repair routines.


#### Features and benefits

- Flexible, contactless data communication
- Clear identification of objects through unique numbering
- Faster data management compared to paper solution
- More accurate documentation processes – prevention of human errors
- Robust and resistant to harsh environments and cleaning processes
- Low frequency (LF – 125 kHz) - Read only
- High frequency (HF – 13.56 MHz) - Rewritable



T50RFID – cable ties with RFID transponder.

<b>MATERIAL</b>	Polyamide 6.6 (PA66)		Polyamide 6.6, UV-resistant (PA66W)
<b>Frequency</b>	125 kHz (LF)	13.56 MHz (HF)	
<b>Idle Temperature</b>	-40 °C to +85 °C		
<b>Operating Temperature</b>	-40 °C to +85 °C	-25 °C to +85 °C	
<b>Flammability</b>	UL 94 V2		



T50RFID, MCTRFD



TYPE	Frequency	Bundle Ø min.	Bundle Ø max.	Width (W)	Length (L)	N	Colour	Pack Cont.	Material	Tools	Article-No.
T50RFIDCLA	125 kHz (LF)	1.5	50.0	4.6	200.0	225	Yellow (YE)	100 pcs.	PA66	6;54	111-01638
T50RFIDCHA	13.56 MHz (HF)	1.5	50.0	4.6	200.0	225	Yellow (YE)	100 pcs.	PA66	6;52-53	111-01639
	13.56 MHz (HF)	1.5	50.0	4.6	200.0	225	Black (BK)	100 pcs.	PA66	6;52-53	111-01591
	13.56 MHz (HF)	1.5	50.0	4.6	200.0	225	Black (BK)	100 pcs.	PA66W	6;52-53	111-02406
	13.56 MHz (HF)	1.5	50.0	4.6	200.0	225	Light Blue (LTBU)	100 pcs.	PA66	6;52-53	111-01673

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

**N** = Minimum Loop Tensile Strength for Cable Ties (Newton)

Recommended Tools				
	6	52	53	54
	EVO7	RFID-DT22-HF	RFID-HS9BT-HF	RFID-HS9BT-LF
	548	515	514	514

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.