



# HT380

## Rugged Handheld Terminal

Offering the latest OS of Android 9, one-handed easy operation and ergonomic keypad design, a long-running 4500mAh battery, the unitech HT380 is a versatile handheld terminal with superior data collection solutions that increases your efficiency in the workplace, suitable for a wide range of applications in manufacturing, retail and inventory management in warehousing.

### Intelligent Imaging Technology

Coming with a superior 2D scanning performance, the HT380 offers 45 degree scanning tilt down design and it's available to capture barcodes from near contact to farther than 60cm away. Base on its ergonomic and lightweight design for one-handed operation, it is suitable to automate the capture of inventory data and allows users to take action quickly and accurately.

### Wireless Communications

Running with Android 9 OS with Qualcomm octa-core CPU, the HT380 is built in a 3.2 inch display for users to check feedback of the scanned information. It also supports Bluetooth® 4.2 and IEEE 802.11 a/b/g/n/ac/d/e/h/i/k/r/v/w dual band standards, allowing enterprises to develop applications or connect to the back-end host to make the database easier, more immediate and more accurate. Furthermore, it has an 8MP camera that gives an easy way for enterprises to proof of delivery or shipment issues.

### Durable for Industrial Applications

Designed for the harsh environments, HT380 is rugged enough to withstand multiple 1.5 meters drop to concrete and built with IP65 environmental seal against water and dust. Another special feature of keypad is the backlight design, providing users with enhanced key location in dark environment. Moreover, the keypad has 2.5 million lifetime clicks and equipped with special silicon materials and PU coating, providing long term abrasion protection. Delivering a 4500mAh changeable battery for business full-day operation, the HT380 is the ideal tool to increase productivity and efficiency in all data collection applications.

### Features

- Android 9 OS with 1.4GHz octa-core processor
- Lightweight and ergonomic one-handed operation
- Superior 2D scanning performance: Support 45 degree scanning tilt down
- Support Bluetooth® 4.2 and IEEE 802.11 a/b/g/n/ac/d/e/h/i/k/r/v/w dual band standards
- Rechargeable and swappable 4500mAh battery for full-day operation
- Durable keypad: 32-keys with 2.5 million lifetime clicks and backlight design
- IP65 rated and 1.5m drop specification.



### System Features

CPU	Octa-core 1.4GHz, Qualcomm 435 (MSM 8940)
Memory	2GB DDR3 RAM, 16GB ROM
OS	Android 9
Languages support	Multi-languages

### Display

3.2" IPS HVGA(480x320) color screen (400 nits), Ultra sensitive capacitive touch screen, compatible with gloves and support wet resistance (400 nits)

### Keypad

32 Keys, SCAN button x 3, 0-9, Up, down, Right, Left, ESC, TAB, BACK, BS, , , P1, P2, Alpha, Fun, F1-F4, Power

### Camera

8MP rear camera with LED flash and auto-focus function

### Indicator

LED, Speaker, Vibrator

### Symbologies

#### 2D CMOS

2D All major 1D and 2D codes (Zebra SE4710 Engine)

#### RFID

HF/NFC Frequency 13.56Mhz (NXP NQ310)  
ISO14443A/B, ISO15693 standard, NFC, MIFARE, Felica

### Regulatory Approvals

CE, RED, FCC, NCC, VCCI

### Communication

USB	Type-C
POGO PIN	Charge only
WLAN	802.11a/b/g/n/ac/d/e/h/i/k/r/v/w
Bluetooth®	Bluetooth® 4.2 + BR/EDR + BLE
GPS	GPS, GLONASS, Galileo, BeiDou

### Power Source

Main battery	Rechargeable 3.85V, 4500mAh Li-ION battery
Operating time	10-12 hours (depending on the specific environment)
RTC battery	RTC backup only

### Expansion Slot

Micro SD/TF x 1(maximum of 128 GB)

### Enclosure

Weight	282g(with battery)
Dimension	182.6 mm x 64.5 mm x 34 mm

### Environmental

Operating temp.	-20°C~50°C
Storage temp.	-30°C~60°C
Charging temperature	0°C to 45°C
Relative humidity	5% ~ 95% (non-condensing)
Drop specification	1.5m
Sealing	IP65

### Accessories

Single-slot cradle with a battery charger



### Headquarters

Taipei, Taiwan  
<http://www.ute.com> e-mail: [info@hq.ute.com](mailto:info@hq.ute.com)

### unitech America

Los Angeles  
<http://us.ute.com> e-mail: [info@us.ute.com](mailto:info@us.ute.com)  
<http://can.ute.com> [info@can.ute.com](mailto:info@can.ute.com)  
Mexico  
<http://latin.ute.com> e-mail: [info@latin.ute.com](mailto:info@latin.ute.com)

### unitech Asia Pacific & Middle East

Taipei  
<http://apac.ute.com> [info@apac.ute.com](mailto:info@apac.ute.com) / [info@india.ute.com](mailto:info@india.ute.com)  
<http://mideast.ute.com> [info@mideast.ute.com](mailto:info@mideast.ute.com)

### unitech Europe

Tilburg / Netherlands  
<http://eu.ute.com> e-mail: [info@eu.ute.com](mailto:info@eu.ute.com)

### unitech Japan

Tokyo  
<http://jp.ute.com> e-mail: [info@jp.ute.com](mailto:info@jp.ute.com)

### unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
<http://cn.ute.com> [info@cn.ute.com](mailto:info@cn.ute.com)  
Taipei <http://tw.ute.com> [info@tw.ute.com](mailto:info@tw.ute.com)

